

DSD-201

Endoscope Reprocessing System

Reprocess



FAST AND FLEXIBLE

AUTOMATED ENDOSCOPE REPROCESSING

EFFICIENT DESIGN FOR QUICK ENDOSCOPE TURNAROUND

- Reprocessing cycle time as short as 28 minutes
- Run simultaneous or independent cycles
- Leak test minimises endoscope repair costs
- Automated alcohol flush and air drying of endoscope channels
- Reprocesses all brands and types of flexible endoscopes

ASSURES PATIENT SAFETY AND REDUCES INFECTION RISK

- Cycle parameters continuously monitored
- Alarm alerts operator of reprocessing deficiency
- Self-disinfects internal fluid lines during every cycle
- Three stage water filtration system

UNPARALLELED OPERATOR SAFETY

- Floating lids contain disinfectant vapors
- No mixing of disinfectant solution
- Virtually no contact between staff and chemicals
- Optional vapor management system

REPROCESS A VARIETY OF ENDOSCOPES

- Compatible with most flexible endoscopes
- Validated for reprocessing TEE probes, dilators, cystoscopes and semi-critical endoscopes

CHOICE OF HIGH-LEVEL DISINFECTANTS

Proven Endoscope Compatibility with:

RAPICIDE™ Disinfectant

- Fast 5-minute contact time @35°C
- Proven endoscope compatibility
- Up to 28-day use life

RAPICIDE™ OPA-28 Disinfectant

- Fast 5-minute contact time @25°C
- 10-minute contact time @20°C
- Proven endoscope compatibility
- Up to 28-day use life



THE COMPLETE CIRCLE OF PROTECTION

As the global vanguard in infection prevention, **only Cantel delivers the Complete Circle of Protection**, a full-value, proactive partnership dedicated to helping you remove risk, streamline operational efficiencies and optimise your success.

REPROCESS High-level disinfection is the cornerstone of infection prevention. Reprocessing technologies from Cantel are designed to ensure patient safety by adhering to the strictest of standards for high-level disinfection, optimise workflow efficiency, and deliver versatility by supporting a wide range of scopes.

ENDOSCOPE REPROCESSING SYSTEM

Simple touch pad operation with LED display



Printed cycle documentation

Dual basins with two independent, asynchronous processing basin



Large basins accommodate all endoscope sizes



Optional Bridge Kit for reprocessing ultrasound endoscopes and TEE Probes/Transducers



DSD-201 Endoscope Reprocessing System

Dimensions

46 H x 36 W x 21 D (inches)

117 H x 91 W x 53 D (cm)

Height with lid open: 64 inches (162.5 cm)

Weight

400 lbs (182 kg)

Electrical Requirements

120VAC, 50/60Hz, 12 amp (North America)

230/240VAC, 50/60Hz, 6 amp (International)

Electrical Safety Certifications

ETL Intertek Listed #75811

UL Standard 61010

CSA/CSA Standard C22.2, No. 601.1

Reservoir Capacities

Disinfectant: 4 gallons (15.1 liters)

Alcohol and detergent: 27oz each (800 ml)

Disinfectant Temperature Range

Room temp to 125°F (52°C)

DSD-201 ordering information

DSD-201 LT

PART NUMBER	DESCRIPTION
DSD-201LT	DSD Endoscope Reprocessor with Leak Tester

DSD-201 LT DISINFECTANT

ML02-0059	RAPICIDE™ High-level Disinfectant and Sterilant
ML02-0120	RAPICIDE™ Potency Indicator Test Strips
ML02-0132	RAPICIDE™ OPA-28 High-level Disinfectant
ML02-0136	RAPICIDE™ OPA-28 Potency Indicator Test Strips
ML02-0125	RAPICIDE™ PA RTU

DSD-201 LT ACCESSORIES

MD01-1001	DSD Mobile Dolly
MK02-0106	INTERCEPT™ Detergent
MK01-0053	Bridge Support Kit

VAPOR MANAGEMENT OPTIONS

DSD-1070R	Passive Vapor Management System
-----------	---------------------------------



INTERCEPT™ and RAPICIDE™ are trademarks of Medivators Inc.

© 2017-2021 Cantel. All Rights Reserved. The Complete Circle of Protection diagram is a trademark owned by Cantel Medical Corp. and is subject to copyright protection owned by Cantel Medical Corp.

www.cantelmedical.eu

Medivators BV | t: +31 (0)45 547 1471 | e: csdistributors@medivators.com

© 2021 Cantel Medical Corp. LIT-00373/B-ENEU

